


ERPEY2.5/4

Width: 6 mm



ERPEY6

Width: 8 mm



2.5-4 mm² Feed Through Terminal Block
Protective Earth, Screw DIN Rail Fixing, Closed
For 35 mm DIN Rail

6 mm² Feed Through Terminal Block
Protective Earth, Screw DIN Rail Fixing, Closed
For 35 mm DIN Rail



Electrical Ratings
CE (EN 60947-7-2)
cRUus
VDE (IEC 60947-7-2)
CSA
IECEX

Voltage, V ~	Current, A	Cross Section
		2.5 - 4 mm ²
300		AWG 26 - 10

Voltage, V ~	Current, A	Cross Section
		6 mm ²
300		AWG 26 - 8

Connection Data
Conductor cross section solid (min.-max.)
Conductor cross section stranded (min.-max.)
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, (min.-max.)
AWG Conductor
Insulation Stripping Length (min.-max.)
Torque (min.-max.)
Rail Tightening Torque (min.-max)
Screwdriver

	0.2 - 0.6 mm ²
	0.2 - 0.6 mm ²
	0.5 - 2.5 mm ²
	AWG 24 - 10
	9 - 10 mm
	0.5 - 0.8 Nm
	0.4 - 0.6 Nm
	0.6 x 3.5

	0.2 - 10 mm ²
	0.2 - 10 mm ²
	0.5 - 4 mm ²
	AWG 24 - 8
	10 - 12 mm
	0.8 - 12 Nm
	0.6 - 0.8 Nm
	0.8 x 4

Technical Data
Rated Impulse Voltage
Insulation material group / Gauge pin code according to IEC 60947-1
Protection class / Protection conductor type

	8/3
	1/A4
	IP 20 / PE

	8/3
	1/B5
	IP 20 / PE

Ordering Data
Feed Through Terminal Block, Earth

Terminal	Qty.	End Plate	Qty.
ERPEY2.5/4	50		

Terminal	Qty.	End Plate	Qty.
ERPEY6	25		

End Bracket
xx: Beige or Grey



Part Number	Qty.	Part Number	Qty.
ES1xx	100		
ES4xx	100		
ES7xx	50		

Part Number	Qty.	Part Number	Qty.
ES1xx	100		
ES4xx	100		
ES7xx	50		

Test Plug and Sockets



Part Number	Qty.	Part Number	Qty.

Part Number	Qty.	Part Number	Qty.


Warning Label
Available in White and Yellow



With Symbol	Qty.	Without Symbol	Qty.

With Symbol	Qty.	Without Symbol	Qty.


Group Marking



Part Number	Qty.	Part Number	Qty.
GE	50		

Part Number	Qty.	Part Number	Qty.

Unprinted Markers



Part Number	Qty.	Part Number	Qty.
MT10/5	500		
MT10/6	500		
MT5	500		

Part Number	Qty.	Part Number	Qty.
DG10/8	160		