

JC1101/NB

X50

X50 Fire rated downlight 3W/5W IP65 3000/4000/5700K 400/650 lm No Bezel

Features & Benefits

- Two wattage and three colour selectable from beneath the ceiling
- Two-part first fix connector with dedicated testing terminals
- Double hinged terminal for easy access to terminal blocks
- Tested for use in Solid, I-Joist and Steel Open Web joist ceilings
- Available in a multipack of 10 with white bezel (JC1101/WH10) or without bezel (JC1101/NB), add bezel with JC1107 (add suffix)



General Information

Mounting	Recessed
Environment	Demanding
Suitable For Zones	Zone 1
Product Group	Fire-rated Downlights
Color Finish	No Bezel
Product Shape	Round
Product Range	X50
Overall Dimensions	84Ø x 55.4 x 322 cm (ssee profile drawing for details)
Length (mm)	322
Height (mm)	55.4
Diameter (mm)	84
Product Weight(kg)	0.245
Light Source	LED
Light Source Features	3CCT Switchable
Additional Information	For Emergency version, use JC131003 only. Not suitable for use with JCEM002/JCEM002ST
Luminaire Accessories	Bezel finish JC1107 * BN/CH/WH/BR/ BLK/ANTH
Recommended product location	Indoor use only
Minimum Void Requirement	50mm
Method of fix	Spring clips
Distance from lighted object	0.3m

Product Aperture Size	68-70mm Ø
IP Rating	IP65
Duration of Fire protection (Mins)	Tested for use in fire-rated ceilings. Full information and upto-date fire testing certificates for ceiling system types are available on JCC.CO.UK
Origin of manufacturer	China
Warranty	5 Year Warranty(Terms & conditions apply)
Dimming Protocol Compatibility	Triac dimmable
Driver manufacturer	JCC
Lighting Product Type 1	Downlight
Lighting Product Type 2	Fire-rated

Electrical

Voltage Rating	230-240
Primary Running Current(Amp)	0.0018/0.0026
Operating Frequency Hz	50/60
Secondary running current(mA)	0.0083/0.0127
Constant Current or Constant Voltage	CC
Luminaire Circuit Wattage	3/5 selectable
Class	I
EMC Compliant (EN55015)	Yes
Input Electrical Connections	Live, Earth, Neutral
Dimmable	Yes, Triac dimmable only

Thermals

Thermal Cut Out	Yes
Insulation Coverage	Loosely Cover with Mineral Wool Insulation
Minimum Void Requirement	50mm
Operating Temperature Range °C	0 to 26

Performance Data

Energy Rating	This product contains a light source of energy efficiency class A
Actual Lumen Output	480/700
Lumens Per Circuit Watt	137/140
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	3000/4000/5700K
Beam Angle °	60°
LOR (Light Output Ratio) %	100
Photometry Available	Yes

Packaging

Product Bar Code EAN-13 Number	5052544121579
--------------------------------	---------------

Standards & Approvals

Manufactured in accordance to

CE Marked

UKCA Marked

Date code/Purchase order No.

WEEE symbol

Certificate Of Conformity

Accredited Members

BS EN 60598:2015, 2-1, 2-2

Yes




Yes

Yes

Yes

available on request

LIA, ISO9001-2015, ISO14001-2015



JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 28 [30/09/2024]