

Datasheet

VIVA-CITY Pro – Adjustable Output



Product Description

Manufactured from the same high-quality materials and using only tier one components, the adjustable VIVA-CITY Pro offers the same great performance but with added versatility.

Using an internal dip-switch, the output is adjustable at any time and offers an output of 20, 40, 60, 80 or 100W making it perfect for maintenance contracts, wholesale stocks and changing needs of sites.


Specification Text

The luminaire shall be manufactured from high-pressure die-cast aluminium. It shall have an LED efficacy of up to 138lm/w and will be capable of producing up to 13800lm luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric forward throw optic and is rated at IP66 and IK08.

Specification

Weight: 6.0 kg
 Windage: 0.07m²
 Material: Die-cast Aluminium
 Paint finish: RAL7016 Anthracite Grey Finish

Optics



Asymmetric Forward Throw Optic 70°

Key Features

- 20W, 40W, 60W, 80W & 100W
- 2760lm – 13800lm
- Efficacy up to 138.0 lm/W
- 4000K, CRI >70
- Lifetime >100,000hr, L80



Mounting Options

- Post Top 60/76mm

Other Options

- Photocell Option on request
[Contact for details](#)

Code	Power (w)	Luminaire Lumens (lm)	Drive Current (mA)	Optic	CCT (K)	IP	IK	Weight (kg)	Paint Finish	Driver Included	Driver Type
VCYP-FW70-4-20-100D	20-100	2760-13800lm	Various	Forward Throw Optic- 70°	4000	IP66	IK08	6.0	RAL7016 Anthracite Grey Finish	Driver Inc	DALI

Dimensions

