PRODUCT DATASHEET
SMART+ WiFi Spot 45° 4.9 W/2700...6500K GU10

SMART+ WiFi SPOT GU10 Multicolour | Reflector shape with WiFi technology



AREAS OF APPLICATION

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Wireless control via app
- Easy to install and use
- Contains no mercury

PRODUCT FEATURES

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 20,000 h



© 2021, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Operating frequency	50…60 Hz
Rated wattage	4.90 W
Power factor λ	> 0.50
Nominal wattage	4.90 W
Nominal voltage	230 V

Photometrical data

Light color (designation)	RGBW
Lumen main.fact.at end of nom.life time	0.70
Adjustable color temperature	2700…6500 K
Rated luminous flux	350 lm
Nominal luminous flux	350 lm
Color rendering index Ra	80

Light technical data

Starting time	< 0.5 s

Dimensions & weight



Product weight	53.00 g
Outer bulb	PAR51
Length	52.0 mm
Diameter	50.0 mm
Overall length	52.0 mm

Lifespan

Rated lamp life time	20000 h
Nominal lamp life time	20000 h

© 2021, LEDVANCE GmbH. All rights reserved.

Lumen maintenance at end of service life	0.70

Additional product data

Mercury-free	Yes
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	GU10

Capabilities

Compatible smart home technology	Google Assistant / Amazon Alexa

Certificates & standards

Energy efficiency class	G

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075485693	Folding carton box 1	61 mm x 78 mm x 96 mm	99.00 g	0.46 dm^3
4058075485709	Shipping carton box 4	173 mm x 108 mm x 141 mm	467.00 g	2.63 dm^3
4058075521476	Shipping carton box 32	359 mm x 229 mm x 303 mm	3984.00 g	24.91 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2021, LEDVANCE GmbH. All rights reserved.