

Product Data Sheet



TRANSCAB LEGRAND

Transcab PVC Open Slot Grey Panel Trunking 25mm x 60mm x 2m Length

REF. 636102 | EAN. 3245066361024

> [Link to e-catalog product sheet](#)

Description

Conforms to EN 50085 Parts 2 and 3, UL and CSA | Material: PVC self-extinguishing or PC/ABS halogen free | Colour: grey RAL 7030 (PVC) or light grey RAL 7035 (PC/ABS) | PC/ABS range passes IEC 695-2-1 850°C glow wire test | Operating temp.: -5 to +60°C | UL classification: UL94 VO | Oxygen index: 43% (PVC) or 37% (PC/ABS) EN ISO 4589 (low fume) | Metric size body in 2 m lengths (6mm gap/6.5mm finger width) | DIN fixing centres of 12.5/25mm | Maximum space for cables with good heat dissipation | Exit cables at terminal or base level

Technical characteristics

| | |
|-------------------|--------------------------|
| Material | Polyvinyl chloride (PVC) |
| Height | 60 mm |
| Width | 25 mm |
| Length | 2000 mm |
| Distance of slots | 6.5 mm |
| Slit width | 6 mm |
| Type of side wall | Hole-/slot punching |
| Halogen free | No |

| | |
|---------------------------------|----------------------|
| Self-extinguishing | Yes |
| Flexible | No |
| Useful cross section | 1159 mm ² |
| Type of fastening | Bottom perforation |
| With cover | Yes |
| Colour | Grey |
| Operating / setting temperature | -5-60 °C |
| Storage temperature | -25-60 °C |

Documents

Technical documentation

F01894EN-02.pdf | PDF (2.49Mo)

Agreements & certificates

UL recogn-E212478 | (0.09Mo)

LGRP-01659-V01.01-EN.pdf | PDF (0.56Mo)

NF 004-641237C | (0.18Mo)

Catalogue pages

industrial-plugs-sockets-enclosures-2020-046.pdf | PDF (0.2Mo)