

Product Data Sheet



TRANSCAB LEGRAND

Transcab PVC Open Slot Grey Panel Trunking 150mm x 100mm x 2m Length

REF. 636123 | EAN. 3245066361239

> [Link to e-catalog product sheet](#)

Description

Conforms to EN 50085 Parts 2 and 3, UL and CSA | Material: PVC self-extinguishing or PC/ABS halogen free | Colour: grey RAL 7030 (PVC) or light grey RAL 7035 (PC/ABS) | PC/ABS range passes IEC 695-2-1 850°C glow wire test | Operating temp.: -5 to +60°C | UL classification: UL94 VO | Oxygen index: 43% (PVC) or 37% (PC/ABS) EN ISO 4589 (low fume) | Metric size body in 2 m lengths (6mm gap/6.5mm finger width) | DIN fixing centres of 12.5/25mm | Maximum space for cables with good heat dissipation | Exit cables at terminal or base level

Technical characteristics

Material	Polyvinyl chloride (PVC)
Height	100 mm
Width	150 mm
Length	2000 mm
Distance of slots	6.5 mm
Slit width	6 mm
Type of side wall	Hole-/slot punching
Halogen free	No

Self-extinguishing	Yes
Flexible	No
Useful cross section	13683 mm ²
Type of fastening	Bottom perforation
With cover	Yes
Colour	Grey
Operating / setting temperature	-5-60 °C
Storage temperature	-25-60 °C

Documents

Technical documentation

 F01894EN-02.pdf | PDF (2.49Mo)

Agreements & certificates

 UL recogn-E212478 | (0.09Mo)

 LGRP-01659-V01.01-EN.pdf | PDF (0.56Mo)

 NF 004-641237C | (0.18Mo)

Catalogue pages

 industrial-plugs-sockets-enclosures-2020-046.pdf | PDF (0.2Mo)