Synergy® white

fused connection units



7300 34



7300 35 + optional red LED power indicator (Cat. No. 7301 58)



7300 30



Bespoke and standard engraving available **p. 41**



7300 36



7301 36



7300 33

Front plates : white thermoset
Terminal screws captive and backed off ready for cabling
Supplied with faceplate screw caps

Pack	Cat. Nos.	Fused connection units 13 A - 250 V~
		Conform to BS 1363 - Part 4 : 1995 Options available as standard with red 'power on' LED indicator LED 'power on' upgrade pack also available Fused 13 A (fuse supplied) Fuse drawer retained by quarter turn catch, drawer padlockable in open position for safety To obtain flush to wall external cord connection on standard depth Cat. Nos. use cord outlet accessory box Cat. No. 7300 53 **p. 38** Flush mounting back box : min. 25 mm deep Nominal plate dimensions : 86 x 86 mm
		Switched
10	7300 34	 Switched, DP
10	7300 35	 Switched, DP with red LED power indicator
10	7300 36	 Switched, DP with cord outlet
10	7300 37	 Switched, DP with cord outlet + red LED power indicator
10	7301 36	 Switched, DP - deep plate with bottom cord outlet

Red power indicator LED pack p. 38

Pack	Cat. Nos.	Fused connection units 13 A - 250 V~ (continued)
		Unswitched
10	7300 30	 Unswitched
10	7300 31	 Unswitched with red LED power indicator
10	7300 32	 Unswitched with cord outlet
10	7300 33	 Unswitched with cord outlet + red LED power indicator

Red power indicator LED pack p. 38

Flush and surface mounting back boxes **p. 39**

