

Synergy® grid system

dimmer, fuse carrier, ancillary modules and decorative rockers



7355 48



7350 30



7352 56



7355 41



7352 65



8326 06

Installation options p. 66
Grid selection charts p. 64-65

Modules mount from front into grid support frames
Individually removable without disturbing grid

Pack	Cat. Nos.	Dimmer unit modules 100-240 V~ 50/60 Hz
1	<div>White</div> <div>7354 46</div> <div>Anthracite</div> <div>7355 46</div>	<p>Conform to BS EN 60669-2-1</p> <p>Dimmer for use with tungsten filament lamps, good quality wire-wound transformers and compatible electronic transformers for low voltage loads¹ 40 - 300 W</p> <p>Not suitable for fluorescent loads</p>

Pack	Cat. Nos.	Dimmer unit modules - dimming HF ballast fluorescent 100-240 V~ 50/60 Hz
1	<div>White</div> <div>7354 48</div> <div>Anthracite</div> <div>7355 48</div>	<p>Conform to BS EN 60669-2-1</p> <p>Leading edge dimmer for potentiometer 0-10 V</p>

Pack	Cat. Nos.	Time delay switch 100-240 V~ 50/60 Hz
1	<div>White</div> <div>7354 47</div> <div>Anthracite</div> <div>7355 47</div>	<p>Conform to BS EN 60669-2-3</p> <p>Multiple way soft start time delay switch Push operated delay pre-set for 3, 10 or 30 minutes 40 - 400 W</p> <p>Not suitable for fluorescent loads</p>

Pack	Cat. Nos.	Fuse carrier modules 13 A - 250 V~
10	<div>White</div> <div>7350 30</div> <div>Anthracite</div> <div>7351 30</div>	<p>Conform to BS 5733</p> <p>Fuse module fitted with BS 1362 13 A fuse</p>

Pack	Cat. Nos.	Indicator modules - 250 V~
1	<div>White</div> <div>7350 60</div> <div>Anthracite</div> <div>7351 60</div>	<p>Conform to BS 5733</p> <p>Indicator - red LEDs</p>
1	<div>White</div> <div>7350 62</div> <div>Anthracite</div> <div>7351 62</div>	<p>Indicator - green LEDs</p>

Pack	Cat. Nos.	Ancillary modules
1	<div>White</div> <div>7354 50</div> <div>Anthracite</div> <div>7355 50</div>	Telephone socket - single master
1	<div>White</div> <div>7354 51</div> <div>Anthracite</div> <div>7355 51</div>	Telephone socket - single secondary
10	7352 56	RJ 45 data outlet CAT 6 compliant
10	7354 40	Rapid cable connection
10	7354 41	UTP 8 contact
10	7354 41	Screened TV - single
10	7352 65	Non-isolated male Ø9.5 mm
10	7354 41	Screened satellite
10	7352 65	Hi-fi outlet - screw terminal
20	7354 36	Blank module

Pack	Cat. Nos.	Decorative rockers - single pole switches 10 AX - 250 V~
1	8326 00	1 way switch
1	8326 06	● Brushed stainless steel
1	8326 12	● Polished stainless steel
1	8326 01	● Gold
1	8326 07	2 way switch
1	8326 13	● Brushed stainless steel
1	8326 02	● Polished stainless steel
1	8326 08	● Gold
1	8326 14	Intermediate switch

Pack	Cat. Nos.	Decorative rockers - single pole switches 20 AX - 250 V~
1	8326 03	1 way switch
1	8326 09	● Brushed stainless steel
1	8326 15	● Polished stainless steel
1	8326 04	● Gold
1	8326 10	2 way switch
1	8326 16	● Brushed stainless steel
1	8326 05	● Polished stainless steel
1	8326 11	● Gold
1	8326 17	2 way retractive centre off switch

Complete range of grid front plates
and support frames p. 64-65

¹ : Can be used in conjunction with compatible electronic transformers for low voltage loads. It will be necessary to test that the dimmer mechanism is compatible with the electronic transformer identified for installation