

Product Data Sheet



ZUCCHINI LB PLUS LEGRAND

Zucchini LB Plus Busbar 25A 4 Conductor 2 Outlet Type A Trunking Length 3m

REF. 75160101 | EAN. 8033777078172

[> Link to e-catalog product sheet](#)

Description

Straight lengths - Type A | Rigid galvanised steel casing | 3 m maximum distance between suspension brackets | Conductors insulated with self-extinguishing plastic (IEC 60695-2-12 and V0 according to UL94) | Standard tap-off outlets with captive IP 55 plug-outlet covers | Protection index: IP 55 | Impact resistance: IK 07

Technical characteristics

| | |
|---|---------|
| Model | Single |
| Rated current AC 50 Hz | 25 A |
| Number of poles | 3 |
| Number of conductors (without earthing) | 4 |
| Flexible | No |
| Rated voltage AC 50 Hz | 0-400 V |

| | |
|---------------------------|---------|
| Number of tap-off units | 2 |
| Colour | Grey |
| Degree of protection (IP) | IP55 |
| Length | 3000 mm |
| Width | 35 mm |
| Height | 46 mm |

Documents

Technical documentation

V0603C.pdf | PDF (6.16Mo)

Agreements & certificates

PEP_LGRP-00636-V02.01-EN.pdf | PDF (0.88Mo)

Catalogue pages

zucchini-busbar-2023-006-007.pdf | PDF (0.05Mo)

zucchini-busbar-2023-008.pdf | PDF (0.22Mo)