

EZ-Path® fire rated pathway Series 33

selection chart


CE marked certification

Fire resistance : EN 1366-3

Classification : EN 13501-2

ETA 18 / 0412

All EZ-Path systems are approved empty up to 100 % visual fill of cable



CM250018 (EZD33T)

Cat. Nos.		Plate kit	Plate dim. (mm) (w x h or Ø)		EZ-Path systems	Opening dimension (mm) (w x h or Ø)	Ø cables (mm)	
1 x CM250018 (1 x EZD33T) (grouted)	1 x	+	–	=		Ø 102 or 90 x 90 (+/- 5 mm)	OD ≤ Ø 21	
2 x CM250018 (2 x EZD33T) (grouted)	2 x	+	–	=		170 x 90 (+/- 5 mm)	OD ≤ Ø 21	
1 x CM250018 + CM250240 (1 x EZD33T + EZP133CWT)	1 x	+	Ø 140	=		Ø 102 or 78 x 78	OD ≤ Ø 21	
							OD ≤ Ø 50	
2 x CM250018 + CM250120 ¹ (2 x EZD33T + EZP233WT)	2 x	+	185 x 109	=		155 x 81	OD ≤ Ø 21	
							OD ≤ Ø 50	
3 x CM250018 + CM250130 ¹ (3 x EZD33T + EZP333WT)	3 x	+	261 x 109	=		230 x 81	OD ≤ Ø 21	
							OD ≤ Ø 50	
4 x CM250018 + CM250140 ¹ (4 x EZD33T + EZP433WT)	4 x	+	407 x 109	=		305 x 81	OD ≤ Ø 21	
							OD ≤ Ø 50	
7 x CM250018 + CM250170 ¹ (7 x EZD33T + EZP733WT)	7 x	+	610 x 109	=		540 x 81	OD ≤ Ø 21	
							OD ≤ Ø 50	
1 x CM250018 + CM250220 (1 x EZD33T + EZP133KT)	1 x	+	Ø 140	=		Ø 102	OD ≤ Ø 21	

Accessories for Series 33

Extension	CM250078 (EZD33E)		Length 152 mm for use with CM250018 (EZD33T)
Dropout	CM250206 (RCM33)		For use with CM250018 (EZD33T)

Fire stopping grommets are available
Contact us on +44 (0) 370 608 9020

For installation, application and fire resistance
data sheets visit
www.legrand.co.uk

NOTE : Please refer to the ETA 18/0412 for additional information about fire resistance classification

1 : Plate kits CM250120 (EZP233WT), CM250130 (EZP333WT), CM250140 (EZP433WT) and CM250170 (EZP733WT) are non-stocked items. Please contact +44 (0) 370 608 9020 for more information.