



90° Angled Wall Mounted Socket Outlets – IP44

- Wall-mounted fixed socket outlet for standard applications.
- Compliance with standards IEC/EN 60309-1/2.
- Rated current from 16A up to 32A.
- Rated voltage option from 110V up to 400V.
- Thermoplastic body with M25 entry.



508146

TOPTER WALL MOUNTED SOCKET, 90° ANGLED, 16A 3P+N+E 380-415V 50-60HZ 6H IP44

TECHNICAL DATA		REGISTRY																			
Rated current	16A	Net weight	0.26KG																		
Rated operating voltage	400V	Min order quantity	1																		
Poles	3P+N+⏏	EAN Code	8014950040179																		
Clock Position	6h	Gross Weight	0.33KG																		
Frequency	50/60Hz	<table><tr><th>REFERENCE STANDARDS</th><th>STANDARDS</th></tr><tr><td>EN 60309-2:1999/A1:2007</td><td>2012/19/EU (WEEE)</td></tr><tr><td>EN 60309-1:1999/A2:2012</td><td>2011/65/EU (RoHS)</td></tr><tr><td>EN 60309-2:1999</td><td>2014/35/EU (LVD)</td></tr><tr><td>EN 60309-1:1999/A1:2007</td><td></td></tr><tr><td>EN 60309-2:1999/A2:2012</td><td></td></tr><tr><td>EN 63000:2018</td><td></td></tr><tr><td>EN 60309-1:1999</td><td></td></tr><tr><td>EN 60309-1:1999/A1AC:2014</td><td></td></tr></table>		REFERENCE STANDARDS	STANDARDS	EN 60309-2:1999/A1:2007	2012/19/EU (WEEE)	EN 60309-1:1999/A2:2012	2011/65/EU (RoHS)	EN 60309-2:1999	2014/35/EU (LVD)	EN 60309-1:1999/A1:2007		EN 60309-2:1999/A2:2012		EN 63000:2018		EN 60309-1:1999		EN 60309-1:1999/A1AC:2014	
REFERENCE STANDARDS	STANDARDS																				
EN 60309-2:1999/A1:2007	2012/19/EU (WEEE)																				
EN 60309-1:1999/A2:2012	2011/65/EU (RoHS)																				
EN 60309-2:1999	2014/35/EU (LVD)																				
EN 60309-1:1999/A1:2007																					
EN 60309-2:1999/A2:2012																					
EN 63000:2018																					
EN 60309-1:1999																					
EN 60309-1:1999/A1AC:2014																					
Protection degree	IP44																				