Twin Socket Outlet - Without Meter



- Circuit Breaker Access Window & Pad lockable
- IEC60309 switched interlocked socket outlets
- Flexible enclosure design allows either 16A or 32A switched interlocked socket to be interchanged on the same fixing flange and wire harness
- Allows for upgrade of additional switched interlocked socket easily and quickly at later date
- IP44 (IP66/IP67 on request)
- High resistance to UV rays and chemical agents
- Smooth undrilled walls allow custom cable entry position

665320

TECHNICAL DATA

Rated current	32A
Rated operating voltage	230V
Outlet Sockets	2 x 16A
Socket Protection	RCBO
Industr. sock.-out. 16A 2P+E 21	
Execution	WALL MOUNTING OR ON SUPPORT

REGISTRY

Net weight	2.25KG
Min order quantity	1
EAN Code	5026992050408
Gross Weight	2.25KG
Dimensions	456x239x173mm (HWD)

REFERENCE STANDARDS

EN 61439-1:2011

EN 61439-2:2011

EN 62053-21:2003

BS 7671:2008

STANDARDS

Lewden
Unit 4, Bradbury Drive, Springwood Industrial Estate - Braintree - Essex - CM7 2SD - UK - Phone: +44 01376 336200 - www.lewden.co.uk - sales@lewden.co.uk