



Multimax - Straight Plug IP67

- Safer than conventional sockets in the same category.
- Compliance with standards IEC/EN 60309-1/2.
- Rated current up to 63A.
- IK08 rating as per IEC/EN 62262.
- Thermoplastic grip material.



710136

MULTIMAX STRAIGHT PLUG 16A 3P+E 380-415V 50-60HZ 6H IP67

| TECHNICAL DATA | | REGISTRY | |
|--|---------------|----------------------------|-------------------|
| Rated current | 16A | Net weight | 0.17KG |
| Frequency | 50/60Hz | EAN Code | 8014950036080 |
| Poles | 3P+ \pm | Gross Weight | 0.18KG |
| Storage room temperature MAX | +70°C | Min order quantity | 1 |
| Protection degree | IP67 | | |
| Nominal Operating Voltage ² | N/A | REFERENCE STANDARDS | STANDARDS |
| Clock Position | 6h | EN 60309-2:1999/A2:2012 | 2011/65/EU (RoHS) |
| Rated operating voltage | 400V | EN 60309-2:1999 | 2014/35/EU (LVD) |
| Manufacturing material | Thermoplastic | EN 63000:2018 | 2012/19/EU (WEEE) |
| | | EN 60309-1:1999/A1AC:2014 | |
| | | EN 50581:2012 | |
| | | EN 60309-1:1999/A1:2007 | |
| | | EN 60309-1:1999/A2:2012 | |
| | | EN 60309-1:1999 | |
| | | EN 60309-2:1999/A1:2007 | |