



Straight Mobile Connector - IP67

- Best use for standard applications.
- Safer than conventional sockets in the same category.
- Compliance with standards IEC/EN 60309-1/2.
- Rated current from 16A up to 63A.
- Rated voltage option from 110V up to 400V.
- IK08 rating as per IEC/EN 62262 with thermoplastic body.



730124

MULTIMAX STRAIGHT CONNECTOR 16A 2P+E 100-130V 50-60HZ 4H IP67

TECHNICAL DATA		REGISTRY																			
Rated current	16A	Net weight	0.18KG																		
Frequency	50/60Hz	Gross Weight	0.20KG																		
Poles	2P+⚡	EAN Code	8014950036141																		
Clock Position	4h	Min order quantity	1																		
Storage room temperature MAX	+70°C	<table><tr><th>REFERENCE STANDARDS</th><th>STANDARDS</th></tr><tr><td>EN 60309-1:1999/A2:2012</td><td>2014/35/EU (LVD)</td></tr><tr><td>EN 60309-2:1999/A2:2012</td><td>2012/19/EU (WEEE)</td></tr><tr><td>EN 60309-1:1999/A1:2007</td><td>2011/65/EU (RoHS)</td></tr><tr><td>EN 63000:2018</td><td></td></tr><tr><td>EN 60309-1:1999/A1AC:2014</td><td></td></tr><tr><td>EN 60309-2:1999</td><td></td></tr><tr><td>EN 60309-2:1999/A1:2007</td><td></td></tr><tr><td>EN 60309-1:1999</td><td></td></tr></table>		REFERENCE STANDARDS	STANDARDS	EN 60309-1:1999/A2:2012	2014/35/EU (LVD)	EN 60309-2:1999/A2:2012	2012/19/EU (WEEE)	EN 60309-1:1999/A1:2007	2011/65/EU (RoHS)	EN 63000:2018		EN 60309-1:1999/A1AC:2014		EN 60309-2:1999		EN 60309-2:1999/A1:2007		EN 60309-1:1999	
REFERENCE STANDARDS	STANDARDS																				
EN 60309-1:1999/A2:2012	2014/35/EU (LVD)																				
EN 60309-2:1999/A2:2012	2012/19/EU (WEEE)																				
EN 60309-1:1999/A1:2007	2011/65/EU (RoHS)																				
EN 63000:2018																					
EN 60309-1:1999/A1AC:2014																					
EN 60309-2:1999																					
EN 60309-2:1999/A1:2007																					
EN 60309-1:1999																					
Protection degree	IP67																				
Rated operating voltage	110V																				
Manufacturing material	Thermoplastic																				