Straight Mobile Connector IP67

- Best use in standard installations/applications.
- Rated current from 16A up to 63A.
- Selection of extra-low and high voltage from 24V up to 400V.
- IK08 as per IEC/EN 62262.
- Thermoplastic body.



730246

MULTIMAX STRAIGHT CONNECTOR 32A 3P+N+E 380-415V 50-60HZ 6H IP67

TECHNICAL DATA	
Rated current	32A
Frequency	50/60Hz
Poles	3P+N+⏚
Clock Position	6h
Storage room temperature MAX	+70°C
Protection degree	IP67
Rated operating voltage	400V
Manufacturing material	Thermoplastic

REGISTRY	
Net weight	0.36KG
Gross Weight	0.38KG
EAN Code	8014950036219
Min order quantity	1

REFERENCE STANDARDS	STANDARDS
EN 60309-2:1999	2011/65/EU (RoHS)
EN 60309-2:1999/A2:2012	2012/19/EU (WEEE)
EN 60309-2:1999/A1:2007	2014/35/EU (LVD)
EN 60309-1:1999/A1AC:2014	
EN 63000:2018	
EN 60309-1:1999/A1:2007	
EN 60309-1:1999/A2:2012	
EN 60309-1:1999	

Lewden
Unit 4, Bradbury Drive, Springwood Industrial Estate - Braintree - Essex - CM7 2SD - UK - Phone: +44 01376 336200 - www.lewden.co.uk - sales@lewden.co.uk