



Vertical Switched Interlocked Socket - With Backbox IP66

- Interlocked socket-outlet for distribution boards.
- Padlockable handle in open or closed position, with max 3 mm Ø padlock.
- Best use for standard installations/applications.
- Rated current from 16A up to 32A.
- Operating voltage option from 110V up to 400V.
- Thermoplastic body.
- Supplied with backbox



PM16/3401NFPB

Switched socket with mechanical interlock

TECHNICAL DATA		REGISTRY																							
Rated current	16A	Net weight	0.76KG																						
Frequency	50/60Hz	Gross Weight	0.90KG																						
Poles	2P+⚡	EAN Code	8014950038176																						
Clock Position	6h	Min order quantity	1																						
Storage room temperature MAX	+70 °C	<table><tr><th>REFERENCE STANDARDS</th><th>STANDARDS</th></tr><tr><td>EN 60309-1:1999/A1AC:2014</td><td>2011/65/EU (RoHS)</td></tr><tr><td>EN 60309-4:2007/A1:2012</td><td>2014/35/EU (LVD)</td></tr><tr><td>EN 60309-4:2007</td><td>2012/19/EU (WEEE)</td></tr><tr><td>EN 60309-1:1999/A1:2007</td><td></td></tr><tr><td>EN 60309-2:1999</td><td></td></tr><tr><td>EN 60309-2:1999/A2:2012</td><td></td></tr><tr><td>EN 60309-1:1999/A2:2012</td><td></td></tr><tr><td>EN 63000:2018</td><td></td></tr><tr><td>EN 60309-1:1999</td><td></td></tr><tr><td>EN 60309-2:1999/A1:2007</td><td></td></tr></table>		REFERENCE STANDARDS	STANDARDS	EN 60309-1:1999/A1AC:2014	2011/65/EU (RoHS)	EN 60309-4:2007/A1:2012	2014/35/EU (LVD)	EN 60309-4:2007	2012/19/EU (WEEE)	EN 60309-1:1999/A1:2007		EN 60309-2:1999		EN 60309-2:1999/A2:2012		EN 60309-1:1999/A2:2012		EN 63000:2018		EN 60309-1:1999		EN 60309-2:1999/A1:2007	
REFERENCE STANDARDS	STANDARDS																								
EN 60309-1:1999/A1AC:2014	2011/65/EU (RoHS)																								
EN 60309-4:2007/A1:2012	2014/35/EU (LVD)																								
EN 60309-4:2007	2012/19/EU (WEEE)																								
EN 60309-1:1999/A1:2007																									
EN 60309-2:1999																									
EN 60309-2:1999/A2:2012																									
EN 60309-1:1999/A2:2012																									
EN 63000:2018																									
EN 60309-1:1999																									
EN 60309-2:1999/A1:2007																									
Protection degree	IP66/IP67																								
Rated operating voltage	230V																								
Manufacturing material	Thermoplastic																								