



# Vertical Switched Interlocked Socket - With Backbox IP66

- Interlocked socket-outlet for distribution boards.
- Padlockable handle in open or closed position, with max 3 mm Ø padlock.
- Best use for standard installations/applications.
- Rated current from 16A up to 32A.
- Operating voltage option from 110V up to 400V.
- Thermoplastic body.
- Supplied with backbox



## PM16/3405NFPB

Switched socket with mechanical interlock

| TECHNICAL DATA               |                    | REGISTRY                  |                   |
|------------------------------|--------------------|---------------------------|-------------------|
| Rated current                | 16A                | Net weight                | 0.81KG            |
| Frequency                    | 50/60Hz            | Gross Weight              | 0.95KG            |
| Poles                        | 3P+ $\frac{N}{PE}$ | EAN Code                  | 8014950038183     |
| Clock Position               | 6h                 | Min order quantity        | 1                 |
| Storage room temperature MAX | +70 °C             |                           |                   |
| Protection degree            | IP66/IP67          | REFERENCE STANDARDS       | STANDARDS         |
| Rated operating voltage      | 400V               | EN 60309-4:2007           | 2011/65/EU (RoHS) |
| Manufacturing material       | Thermoplastic      | EN 60309-2:1999/A2:2012   | 2014/35/EU (LVD)  |
|                              |                    | EN 60309-2:1999/A1:2007   | 2012/19/EU (WEEE) |
|                              |                    | EN 60309-1:1999/A1:2007   |                   |
|                              |                    | EN 63000:2018             |                   |
|                              |                    | EN 60309-2:1999           |                   |
|                              |                    | EN 60309-4:2007/A1:2012   |                   |
|                              |                    | EN 60309-1:1999/A2:2012   |                   |
|                              |                    | EN 60309-1:1999/A1AC:2014 |                   |
|                              |                    | EN 60309-1:1999           |                   |