



Straight Plug IP44

- Designed for ease of assembly and wiring.
- Twist grip cable gland locking system.
- Rated current up to 32A.
- IK08 rating as per IEC/EN 62262.
- Thermoplastic grip material.



PM32/1800FPB

MULTIMAX PLUG 3P+N+E 32A 6H IP44 400V

TECHNICAL DATA		REGISTRY	
Rated current	32A	Net weight	0.23KG
Frequency	50/60Hz	EAN Code	8014950031498
Poles	3P+N+ $\frac{1}{2}$	Gross Weight	0.26KG
Protection degree	IP44	Min order quantity	1
Nominal Operating Voltage2	N/A		
Clock Position	6h	REFERENCE STANDARDS	STANDARDS
Rated operating voltage	400V	EN 63000:2018	2012/19/EU (WEEE)
Manufacturing material	Thermoplastic	EN 60309-1:1999/A2:2012	2014/35/EU (LVD)
		EN 50581:2012	2011/65/EU (RoHS)
		EN 60309-2:1999/A2:2012	
		EN 60309-2:1999/A1:2007	
		EN 60309-1:1999/A1:2007	
		EN 60309-2:1999	
		EN 60309-1:1999	
		EN 60309-1:1999/A1AC:2014	