



Vertical Switched Interlocked Socket - With Backbox IP66

- Interlocked socket-outlet for distribution boards.
- Padlockable handle in open or closed position, with max 3 mm Ø padlock.
- Best use for standard installations/applications.
- Rated current from 16A up to 32A.
- Operating voltage option from 110V up to 400V.
- Thermoplastic body.
- Supplied with backbox



PM63/3401FPB

Switched socket with mechanical interlock

TECHNICAL DATA		REGISTRY	
Rated current	63A	Net weight	2.36KG
Frequency	50/60Hz	Gross Weight	2.50KG
Poles	2P+ $\overline{\text{N}}$	EAN Code	8014950035007
Clock Position	6h	Min order quantity	1
Storage room temperature MAX	+70°C		
Protection degree	IP65	REFERENCE STANDARDS	STANDARDS
Rated operating voltage	230V	EN 63000:2018	2014/35/EU (LVD)
		EN 60309-1:1999/A2:2012	2012/19/EU (WEEE)
		EN 60309-2:1999/A1:2007	2011/65/EU (RoHS)
		EN 60309-2:1999/A2:2012	
		EN 60309-4:2007	
		EN 60309-4:2007/A1:2012	
		EN 60309-2:1999	
		EN 60309-1:1999/A1AC:2014	
		EN 60309-1:1999/A1:2007	
		EN 60309-1:1999	