Vertical Switched Interlocked Socket - With Backbox IP66



- Interlocked socket-outlet for distribution boards.
- Padlockable handle in open or closed position, with max 3 mm Ø padlock.
- Best use for standard installations/applications.
- Rated current from 16A up to 32A.
- Operating voltage option from 110V up to 400V.
- Thermoplastic body.
- Supplied with backbox

PM63/3408FPB

Switched socket with mechanical interlock

TECHNICAL DATA	
Rated current	63A
Frequency	50/60Hz
Poles	3P+N+⏚
Clock Position	6h
Storage room temperature MAX	+70°C
Protection degree	IP65
Rated operating voltage	400V

REGISTRY	
Net weight	2.61KG
Gross Weight	2.74KG
EAN Code	8014950035021
Min order quantity	1

REFERENCE STANDARDS	STANDARDS
EN 60309-1:1999	2011/65/EU (RoHS)
EN 60309-1:1999/A2:2012	2014/35/EU (LVD)
EN 63000:2018	2012/19/EU (WEEE)
EN 60309-1:1999/A1AC:2014	
EN 60309-2:1999/A1:2007	
EN 60309-4:2007/A1:2012	
EN 60309-2:1999	
EN 60309-1:1999/A1:2007	
EN 60309-4:2007	
EN 60309-2:1999/A2:2012	