



light safe
emergency lighting systems

ERLEDB

LED BULKHEAD C/W MULTI LEGEND



Also Available

Auto Self-Test Version - ERLEDBT

- **Operation:** Switchable Maintained
- **Consumption:** 6W
- **IP:** IP65
- **Emergency Duration:** >3hrs
- **Colour Temperature:** 6500K

- **Battery Type:** Ni Cd
- **Battery Size:** 3.6v 800mAH
- **Accessories supplied:** Legend Pack
- **Standards:** EN-60598-2-22
- **Dimensions:** (L)353mm x (W)110mm x (H)65mm



LED BULKHEAD C/W MULTI LEGEND

SPECIFICATIONS

Operation	Switchable Maintained
Voltage	230v AC 50Hz
Consumption	6W
Max Cable Size	2 x 1.5mm ²
Class	1
Emergency Duration	>3hrs
Colour Temperature	6500K
Lumen Output Mains	300lm
Lumen Output Emergency	110lm
Battery Type	Ni Cd
Battery Size	3.6v 800mAH
LED Qty	8pcs
LED Brand	Epistar
LED Type	5730
Recharge Time	24 hours
Temp Range	0°C - 40°C
Base Material	Polycarbonate
Diffuser Material	Polycarbonate
Gear Tray	Polycarbonate
Weight	525g
Accessories supplied	Legend Pack
IP	IP65
Standards	EN-60598-2-22
Dimensions	(L)353mm x (W)110mm x (H)65mm

FIXTURE SPACING INFORMATION

1 LUX (ESCAPE ROUTES)

	End Towards Wall	End to End	Parallel to Wall	Side to Side
Height				
2.0m	2.61	5.99	2.40	6.89
2.5m	2.68	6.82	2.29	6.23
3.0m	2.41	7.41	1.99	6.99
3.5m	2.59	7.67	2.17	6.25
4.0m	2.62	6.83	1.80	5.32
5.0m	1.77	7.47	1.22	6.07
6.0m	0.79	6.12	0.13	5.25

0.5 LUX (OPEN AREA)

	End Towards Wall	End to End	Parallel to Wall	Side to Side
Height				
2.0m	2.79	4.63	2.61	6.24
2.5m	2.81	6.30	2.47	7.77
3.0m	3.07	5.22	2.62	6.09
3.5m	3.05	5.57	2.63	5.23
4.0m	3.08	7.91	2.27	7.39
5.0m	3.38	8.06	2.49	6.97
6.0m	3.92	7.62	1.07	6.36

Using photometric data after 3 hour test

