

LK3237 series fan-and-filter

116.5x116.5mm | 25-35 m³/h






Colour	RAL7035,color can be customized
Protection category	IP54 standard, IP55 plus precision filter mat, IP56 plus precision filter mat and protective cover.



Dimensions

Exit filter LK 3237.300



Model No.fan-and-filter unit LK	3237.230-LK	3237.115-LK	3237.024-LK
Model No.fan-and-filter unit EMC	3237.230-EMC	3237.115-EMC	3237.024-EMC
Rated operating voltage,frequency V,Hz	230V, 50/60Hz	115V, 50/60Hz	24V (DC)
Air throughput,unimpeded air flow	25-35 m ³ /h		35 m ³ /h
Air throughput with Exit filter including standard filter mat	1 x LK 3237.300: 20-25 m ³ /h		
Axial fan	Self-starting shaded pole motor		DC motor
Rated current max.	0.08 A	0.14 A	0.18 A
Rated Power	18.0-14.0 W		4.3 W
Noise level	37-41 dB(A)		41 dB(A)
Operating temperature range	-30 - +70 °C		
Model No. Exit filter LK / EMC	3237.300 / 3237.300-EMC		
Design	Made of injection-moulded thermoplastic, customizable flame retardant materials, consistent with UL94-V0 self-extinguishing.		