

Combo Kit CXT® CLX228AJ

12Vmax

CXT® powered Combo Kit

Includes : HP333D Combi Drill + TD110D Impact Driver. Two 2.0 Ah batteries and a charger.



Models in kit



**Combi Drill CXT®
HP333D**



**Impact Driver CXT®
TD110D**

Combi Drill CXT®

HP333D

12V max • 30 Nm • 0 – 1 700 min⁻¹

A compact, brushless drill for professional screwdriving and drilling

A lightweight drill for screwdriving and drilling with or without hammer action, two power settings. Maximum torque of 30 / 14 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light.



■ Technical specifications

CXT Battery	✓
Battery protection	✓
No load speed	0 - 450 / 0 - 1700 min ⁻¹
Impacts per Minute (IPM)	0 - 6750 / 0 - 25 500 min ⁻¹
Max. fastening torque Hard/Soft	30 / 14 Nm
Clutch torque setting	20
Max. Drilling Diameter in Wood	21 mm
Max. Drilling Diameter in Masonry	8 mm
Max. Drilling Diameter in Concrete	8 mm
Max. Drilling Diameter in Steel	10 mm
Drill Chuck Capacity	0,8 - 10 mm
Sound Power Level (L _{WA})	93 dB(A)
Sound Pressure Level (L _{pA})	82 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

■ User benefits

- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Impact Driver CXT®

TD110D

12Vmax • 1/4" • 110 Nm • 0 – 2
600 min⁻¹

Impact driver for tight spaces

A compact and light impact wrench with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a high fastening torque of up to 110 Nm. A handy LED light for added lighting.



Technical specifications

CXT Battery	✓
Battery protection	✓
No load speed	0 - 2600 min ⁻¹
Max Fastening Torque Impact Drill	110 Nm
Tightening Capacity Standard Bolt	M5 - M12
Impacts per Minute (IPM)	0 - 3500 min ⁻¹
Sound Power Level (L _{WA})	105 dB(A)
Sound Pressure Level (L _{pA})	94 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	8 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	1,0 - 1,2 kg
Product Dimensions (L x W x H):	153 x 66 x 204 mm
Nominal Battery Voltage	12 V
Charging Time 1.5 Ah	22 min

User benefits

- The rubber coating on the handle ensures a firm working grip
- LED light illuminates the work site

Link to product - www.makita.com



Related products kit

Standard AC

251314-2

Truss Head Screw M4*12, Td140D

346909-5 (2x)

Belt Hook

784244-7 (2x)

Screw Bit, Ph2 – Ph2, 50 Mm, Double

266622-8

Truss Head Screw M4 X 12

687329-7

Band

821549-5

Makpac case (1)



Standard MA

BL1021B (2x)

Battery CXT® 2,0 Ah

DC10WD

Battery Charger CXT®



Optional AC

266622-8

Truss Head Screw M4 X 12

456128-6

Battery Cover CXT®

784244-7

Screw Bit, Ph2 – Ph2, 50 Mm, Double

BL1021B

Battery CXT® 2,0 Ah

D-42204

COUNTERSINK 6PC SET

D-47363

Forstner Drill Bit Set, 5 pcs



346909-5

Belt Hook

784244-7

Screw Bit, Ph2 – Ph2, 50 Mm, Double

821549-5

Makpac case (1)

B-12326

Torsion screw bit PH2 – PH2, 85 mm,

BL1021B

Battery CXT® 2,0 Ah

DEAADP08

USB Adaptor CXT



Other - HP333D

[User manual](#)

[Parts drawing](#)

 **Other - TD110D**

User manual

Parts drawing