

Auto Feed Screwdriver LXT®

DFR551Z

18V • 25 - 55 mm • 0 - 6 000 min⁻¹

For very fast screw driving with a reliable feeder.

DFR551 has Push Drive Technology; The motor rotates at full speed only when the screw is pressed against the board to reduce power consumption and noise.



Technical specifications

Vibration Level, Screwdriving Without Impact	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Screwdriving Without Impact	1,5 m/s ²
Voltage LXT	✓
Nominal Battery Voltage	18 V
Max Output Power	440 W
No load speed	0 - 6000 min ⁻¹
Driving Shank	1/4 "
Capacity Drywall Screw	3,5 - 4,2 mm
Collated drywall screw	25 - 55 mm
Sound Pressure Level (L _{pA})	74 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Product net weight	1,6 kg
Tool weight with battery	1,9 - 2,2 kg
Product Dimensions (L x W x H):	396 x 88 x 211 mm
Brushless Motor	✓

User benefits

- Brushless maintenance-free and long-life motor
- Extreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Ergonomically designed handle with rubberised soft grip
- Practical hanging hook
- Variable speed
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381751230

Link to product - www.makita.com



Related products

■ Standard AC

266622-8
Truss Head Screw M4 X 12



346317-0
Belt Hook



■ Optional AC

266622-8
Truss Head Screw M4 X 12



346317-0
Belt Hook



■ Other

[User manual](#)

[Parts drawing](#)