

Combi Drill LXT®

DHP482RTJ

18V • 62 Nm • 0 – 1 900 min⁻¹

Powerful general-use combi drill with hammer action for professionals

An efficient drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 62 / 36 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Two 5.0 Ah batteries and a charger in Makpac case included.



■ Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 600 / 1900 min ⁻¹
Max. fastening torque Hard/Soft	62 / 36 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 9000 / 28500 min ⁻¹
Max. Drilling Diameter in Wood	38 mm
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	60 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Concrete	13 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Electronic brake	✓

■ User benefits

- 4-pole motor in compact design without torque loss at low power consumption
- Highly efficient and compact machine for professional use
- Optimal handle design
- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site

■ **EAN 0088381813631**

Link to product - www.makitauk.com



Related products

Standard AC

346317-0
Belt Hook



821550-0
Makpac case (2)



Standard MA

BL1850B (2x)
Battery LXT® 5,0 Ah



DC18RC
Battery Charger LXT®



Optional AC

196311-0
Keyless Drill Chuck, 13 mm



251314-2
Truss Head Screw M4*12, Td140D



346317-0
Belt Hook



784637-8
Screw Bit, Ph2 – S6, 45 Mm, Double



821550-0
Makpac case (2)



837916-4
MakPac (2) Inlay



D-72877
Drill bit set T.C.T, 5 pcs



Other

[User manual](#)

[Parts drawing](#)