

# Rotary Hammer LXT®

## DHR202RT1J

18V • SDS-Plus • 20 mm • 2.0 J

### Professional three-mode rotary hammer

An efficient combi hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 1 100 min<sup>-1</sup>. Impact energy of 2.0 J and max. drilling capacity of 20 mm in concrete



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 min <sup>-1</sup>
Impacts per Minute (IPM)	0 - 4000 min <sup>-1</sup>
Max. Drilling Diameter in Wood	26 mm
Max. Drilling Diameter in Concrete	20 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	4 - 12 mm
Impact Energy	1,9 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L <sub>WA</sub> )	99 dB(A)

### User benefits

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- Reversing switch
- Reversing switch is conveniently located
- Compact and lightweight for reduced operator fatigue
- One touch sliding chuck enables quick and easy bit changes

**EAN 0088381720731**

Link to product - [www.makitauk.com](http://www.makitauk.com)



# Related products

## Standard AC

324219-0  
Depth Gauge

821551-8  
Makpac case (3)



## Standard MA

BL1850B  
Battery LXT® 5,0 Ah



DC18RC  
Battery Charger LXT®



## Optional AC

324219-0  
Depth Gauge

821551-8  
Makpac case (3)



837634-4  
MakPac (3) Inlay



## Other

User manual

Parts drawing