

Rotary Hammer LXT®

DHR242RTJW

18V • SDS-Plus • 24 mm • 2.0 J

Professional brushless, three-mode rotary hammer with dust extraction

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle and dust extraction. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min⁻¹. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete. Two 5.0Ah batteries and a rapid charger in a Makpac case.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 950 min ⁻¹
Impacts per Minute (IPM)	0 - 4700 min ⁻¹
Max. Drilling Diameter in Wood	27 mm
Max. Drilling Diameter in Concrete	24 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	6 - 12 mm
Impact Energy	2,0 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L _{WA})	101 dB(A)

User benefits

- Brushless maintenance-free and long-life motor
- Low power consumption thanks to brushless motor
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381876094

Link to product - www.makita.com



Related products

Standard AC

821552-6

Makpac case (4)



199563-2

Dust Extraction System DX06



324219-0

Depth Gauge



424474-5 (5x)

Sealing Cap



450128-8

Battery cover, LXT®, 14,4 – 18V



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

821552-6

Makpac case (4)



D-16368

Chisel set SDS-PLUS, 5 pcs



199557-7

Replacement Hepa filter



196165-5

HEPA filter



424474-5

Sealing Cap



835A31-4

MakPac Type 4 Inlay



Other

User manual

Parts drawing