

Rotary Hammer LXT®

DHR243Z

18V • SDS-Plus • 24 mm • 2.0 J

Brushless, three-mode rotary hammer with quick-change chuck

An efficient rotary hammer with an anti-vibration handle and quick-change chuck that accepts SDS-Plus bits. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min⁻¹. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 950 min ⁻¹
Impacts per Minute (IPM)	0 - 4700 min ⁻¹
Max. Drilling Diameter in Wood	27 mm
Max. Drilling Diameter in Concrete	24 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	6 - 12 mm
Impact Energy	2,0 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L _{WA})	100 dB(A)

User benefits

- Brushless maintenance-free and long-life motor
- Impact drilling, non-impact drilling and spike function
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381654722

Link to product - www.makita.com



Related products

Standard AC

194079-2

Quick Change Drill Chuck 13 mm,



324219-0

Depth Gauge



Optional AC

195180-6

Dust Collecting Cap



196165-5

HEPA filter



196173-6

Exchangeable chuck set



199977-5

Hepa Filter



324219-0

Depth Gauge



424474-5

Sealing Cap



821552-6

Makpac case (4)



835A31-4

MakPac Type 4 Inlay



837649-1

MakPac (4) Inlay



D-16368

Chisel set SDS-PLUS, 5 pcs



Other

[User manual](#)

[Parts drawing](#)