

Rotary Hammer LXT®

DHR264ZJ

18V X2 • SDS-Plus • 26 mm • 2.5 J

Three-mode rotary hammer with quick-change chuck

An efficient rotary hammer with anti-vibration rear and side handles, for SDS-Plus bits. Suited to impact and unstressed drilling and chipping. Speed range of 0 – 1 200 min⁻¹. Impact energy of 2.5 J and max. drilling capacity of 26 mm in concrete. Tool only, battery and charger not included. Comes in a MakPac case.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	2 x 18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1250 min ⁻¹
Impacts per Minute (IPM)	0 - 5000 min ⁻¹
Max. Drilling Diameter in Wood	32 mm
Max. Drilling Diameter in Concrete	26 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	4 - 18 mm
Impact Energy	2,5 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Sound Power Level (L _{WA})	102 dB(A)
Sound Pressure Level (L _{pA})	94 dB(A)

EAN 0088381663694

Link to product - www.makita.com

User benefits

- 36V performance from two 18V batteries connected in series. The batteries are placed in parallel in separate battery docking stations.
- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- One touch sliding chuck enables quick and easy bit changes
- Ergonomic chassis design ensures a good working position.
- Reversing switch
- LED light illuminates the work site
- Battery protection circuit protects against overloading, over-discharging and over-heating



Related products

Standard AC

142729-3
Makpac Type 4



194079-2
Quick Change Drill Chuck 13 mm,



194683-7
Grease vessel set, 100 ml



324219-0
Depth Gauge



443122-7
Cleaning Cloth



821552-6
Makpac case (4)



Optional AC

193472-7
Dust extraction set Ø 25 / 31 mm



194079-2
Quick Change Drill Chuck 13 mm,



194683-7
Grease vessel set, 100 ml



324219-0
Depth Gauge



837988-9
MakPac (4) Inlay



Other

[User manual](#)

[Parts drawing](#)