

2 Piece Combo Kit XGT®

DK0176G205

40V

Includes TD003G Brushless Impact Driver, HP001G
Brushless Combi Drill



Models in kit



**Combi Drill XGT®
HP001G**



**Impact Driver XGT®, 40Vmax
TD003G**

Combi Drill XGT®

HP001G

40V max • 140 Nm • 0 – 2 600 min⁻¹

Rugged, brushless combi drill for heavy-duty screwdriving and drilling

A powerful, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. A high maximum torque of 140 / 68 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light.



Technical specifications

Nominal Battery Voltage	40 V
Voltage XGT	✓
Brushless Motor	✓
No load speed	0 - 650 / 2600 min ⁻¹
Max. fastening torque Hard/Soft	140 / 68 Nm
Torque setting	41 / 21
Impacts per Minute (IPM)	0 - 9750 / 39000 min ⁻¹
Max. Drilling Diameter in Wood	76 mm
Max. Drilling Diameter in Masonry	20 mm
Max. Drilling Diameter in Steel	20 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	96 dB(A)
Sound Pressure Level (L _{pA})	85 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

User benefits

- Jog selector for easy adjustment of mounting torque, visual confirmation of the selected torque on the digital display
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- Battery protection system automatically shuts off power when the battery level is low
- Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops

[Link to product - www.makita.com](http://www.makita.com)



Impact Driver XGT®, 40Vmax

TD003G

1/4", 210 Nm, 0 – 3 700 min⁻¹

Model TD003G is a cordless impact driver powered by 40Vmax XGT® Li-Ion battery

It features a combination of sufficient fastening performance and high cost-competitiveness achieved by carefully selecting the functions. The main features and benefits are: •Aluminum hammer case + Black bumper •Impact power selection: · 4 modes (Max/ Hard/ Med./ Soft for bolt) · 1 T-mode (for thin metal only)



Technical specifications

Nominal Battery Voltage	40 V
Voltage XGT	✓
Brushless Motor	✓
No load speed	0 - 1100 / 2100 / 3200 / 3700 min ⁻¹
Max Fastening Torque Impact Drill	20 / 50 / 170 / 210 Nm
Tightening Capacity Standard Bolt	M5 - M16
Impacts per Minute (IPM)	0 - 1400 / 2600 / 3600 / 4100 min ⁻¹
Sound Power Level (L _{WA})	106 dB(A)
Sound Pressure Level (L _{pA})	95 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	11,9 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery	1,7 - 2,9 kg

User benefits

- LED light illuminates the work site
- Low power consumption thanks to brushless motor
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- The rubber grip on the handle ensures a good working grip
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makita.com



Related products kit

Standard AC

821551-8

Makpac case (3)



Standard MA

BL4025 (2x)

Battery XGT® 2,5 Ah



DC40RA

Battery Charger XGT®



Optional AC

122576-8

Stopper Pole



127551-9

Grip Assembly



346317-0

Belt Hook



452947-8

Bitholder



763252-1

Keyless Drill Chuck



784637-8

Screw Bit, Ph2 – S6, 45 Mm, Double



821551-8

Makpac case (3)



835F93-2

Inner tray (3)



BL4025

Battery XGT® 2,5 Ah



BL4040

Battery XGT® 4,0 Ah



Other - HP001G

User manual

Parts drawing

Other - TD003G

User manual

Parts drawing