2 Piece Combo Kit LXT®,

DLX2566TJ

18V

Includes: DHP492 Combi Drill and DTD201 Impact Driver, 2 x 5.0Ah batteries, Fast Charger, Makpac case



Models in kit



Combi Drill LXT®
DHP492



18V Impact Driver LXT®
DTD201

Combi Drill LXT®

DHP492

18V

A powerful, brushless general-use impact drill for screwdriving and drilling

An efficient, brushless drill for screwdriving and drilling. A powerful max. torque of 141Nm. The main feature and benefits are: Redesigned speed change mechanism to avoid gear disengagement, Controller protection has been revised to enhance the protection for electronic components during variable speed control by the trigger.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Brushless Motor	✓
No load speed	0 - 550 / 2100 min^{-1}
Max. fastening torque Hard/Soft	130 / 65 Nm
Max Torque	141 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 8250 / 31500 min^{-1}
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Wood (Auger Bit)	50 mm
Drilling Capacity Wood (Self-feed bit)	76 mm
Drilling Capacity Flat bit	40 mm
Drilling Capacity Hole Saw	152 mm
Driving Shank	1/2"-20UNF "

User benefits

- Highly efficient and compact machine for professional use
- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low
- Electronic overload protection protects the user and the device
- Keyless chuck for easy bit installation and removal
- Compact and lightweight for reduced operator fatigue
- Electric brake for maximum productivity and increased operator safety

Link to product - www.makitauk.com

18V Impact Driver LXT®

DTD201

1/4", 210 Nm, 0 – 3 700 min^{-1}

Model DTD201 is an impact driver powered by a 18V LXT Li-Ion battery.

This machine delivers higher maximum fastening torque. enabling high speed, high power operation even in heavy duty applications such as fastening hex coach screws and hardware screws.



Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 / 2100 / 3200 / 3700 min^{-1}
Max Fastening Torque Impact Drill	20 / 150 / 190 / 210 Nm
Impacts per Minute (IPM)	0 - 2000 / 3600 / 4200 / 4400 min^{-1}
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Driving Shank	1/4 "
Sound Power Level (L_{WA})	105 dB(A)
Sound Pressure Level (L_{pA})	97 dB(A)

User benefits

- Low power consumption thanks to brushless motor
- Quick mount for 1/4 "screwdriver
- LED light illuminates the work site
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Electric brake for maximum productivity and increased operator safety
- The rubber coating on the handle ensures a firm working grip
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makitauk.com

Related products kit

Standard AC

821551-8
Makpac case (3)



Standard MA

BL1850B (2x)
Battery LXT® 5,0 Ah



DC18RC
Battery Charger LXT®



Optional AC

122576-8
Stopper Pole

122D10-2
Grip Assembly

821550-0
Makpac case (2)



837916-4
MakPac (2) Inlay



Other - DHP492

User manual

Parts drawing

Other - DTD201

User manual

Parts drawing