

# Circular Saw LXT ®

## DSS611Z

18 V • 3 700 min<sup>-1</sup> • 165 mm



**LXT** 18V

### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	3700 min <sup>-1</sup>
Max. Cutting Depth at 45°	40 mm
Max. Cutting Depth at 50°	36 mm
Max. Bevel Range (Left)	0 / 45 °
Blade Diameter	165 mm
Bore Size (Arbor Diameter)	15,88 / 20 / 25,4 / 30 mm
Tool weight with battery (EPTA)	2,9 - 3,2 kg
Product Dimensions (L x W x H):	347 x 202 x 228 mm
Plastic Carrying Case	✓
Blade Diametre	165 mm

### User benefits

- Smooth cutting at high rotational speed of 3,700 RPM
- Easy to grip, ergonomically designed handle with soft grip provides a sure and comfortable grip
- Safety cover with calibration line for adjusting cutting depth
- Bevel cuts 0° - 45°
- Large bevel lock lever; Easy to operate even if the machine is placed close to the wall, because you do not need to reach for the rear of the machine to turn the lever
- Externally accessible brushes for easy serviceability

**EAN 0088381663014**

[Link to product - www.makitauk.com](http://www.makitauk.com)



# Related products

## ■ Standard AC

**164095-8**  
Parallel Guide



**726096-0**  
Carbide Tipped Saw Blade 165

**783203-8**  
Hex Wrench 5 Mm



---

## ■ Other

User manual