

18V Impact Driver BL LXT

DTD154Z

Model DTD154 is a Cordless Impact Driver powered by 18V Li-ion battery and developed based on DTD148.

18V Impact Driver BL LXT



TECHNICAL SPECIFICATIONS

| | |
|------------------------------|-------------------------|
| Voltage | 18 v |
| Standard Bolt | M5-M16 |
| High Tensile Bolt | M5-M14 |
| Coarse thread (length) | 22 - 125 mm |
| Max Fastening Torque | 175 Nm |
| Battery Type | Lithium-ion |
| Vibration: Fastening Bolt | 12.5 m/sec ² |
| Vibration K factor | 1.5 m/sec ² |
| Noise sound pressure | 96 dB(A) |
| Noise sound power | 107 dB(A) |
| Noise K factor | 3 dB(A) |
| Body only machine | ✓ |
| Net weight | 1.2 - 1.5 kg |
| Battery Quantity (5.0ah) | 0 |
| Impact Selection | 3 stage + Tek mode |
| Driving Shank | 6.35mm (1/4") Hex |
| Blows per Minute (Hi) - ipm | 0 - 3800 ipm |
| Blows per Minute (Med) - ipm | 0 - 2600 ipm |

USER BENEFITS

- T-mode: Tightening mode for self-drilling screw
- Electronic 3-stage impact power selection (Hard/ Medium/Soft)
- Brushless motor
- LED job light
- Ergonomic soft grip
- Electric brake
- Variable speed control by trigger
- Forward / reverse rotation
- Compact overall length.

[Link to product - makitauk.com](https://www.makita.com)



RELATED PRODUCTS

(Recon

■ OTHER