

Impact Driver LXT®

DTD172Z

18V • 1/4" • 180 Nm • 0 – 3 600 min⁻¹

Compact brushless impact driver for quick driving

A compact and light impact wrench with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 180 Nm, suitable for quick driving. A handy LED light for added lighting. Tool only, battery and a charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 / 2100 / 3200 / 3600 min ⁻¹
Max Fastening Torque Impact Drill	180 Nm
Tightening Capacity Standard Bolt	M5 - M16
Impacts per Minute (IPM)	0 - 1 100 / 2 600 / 3 600 / 3 800 min ⁻¹
Sound Power Level (L _{WA})	108 dB(A)
Sound Pressure Level (L _{pA})	97 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	13,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product net weight	0,85 kg

User benefits

- Soft grip provides increased comfort on the job
- Redesigned mode selection switch for one-handed mode selection
- Anti-bit wobbling structure; Two ball bearings are used to securely hold the anvil for reduced bit wobbling
- Brushless motor efficiently uses energy to match torque and RPM to the changing demands of the application
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381748995

Link to product - www.makita.com



Related products

Standard AC

266622-8

Truss Head Screw M4 X 12



346317-0

Belt Hook



Optional AC

266622-8

Truss Head Screw M4 X 12



346317-0

Belt Hook



821550-0

Makpac case (2)



837670-0

MakPac (2) Inlay



Other

[User manual](#)

[Parts drawing](#)