

18V Angle Impact Driver LXT

DTL061Z

Compact angle head for easy access in tight places.

18V Angle Impact Driver LXT



TECHNICAL SPECIFICATIONS

Voltage	18 v
Drive hex	1/4 "
Machine Screw Size	M4-M8 mm
Standard Bolt	M4-M12
High Tensile Bolt	M4-M8
Coarse thread (length)	22 - 75 mm
Impacts	0 - 3000 ipm
No Load Speed	0 - 2000 rpm
Max Torque	60 Nm
Battery Type	Lithium-ion
Battery Quantity (3.0 Ah)	0
Vibration: Fastening Bolt	11 m/sec ²
Vibration K factor	1.5 m/sec ²
Noise sound pressure	90 dB(A)
Noise sound power	101 dB(A)
Noise K factor	3 dB(A)
Body only machine	✓
Net weight	1.4 - 2.0 kg

USER BENEFITS

- 22 minute charge time with the air cooled Makstar Optimum Charging System.
- 4 pole motor.
- Keyless single sleeve hex chuck.
- Lithium-ion's 40% weight saving means 18 volt power can be obtained by a battery that weighs the same as a 12 volt Ni-MH battery.
- Lithium-ion batteries have greater life spans than their Ni-MH or Ni-Cad counterparts giving 430% greater run time.
- Large trigger.

[Link to product - makitauk.com](https://www.makita.com)



RELATED PRODUCTS

(Reco

■ OTHER