

Angle Impact Wrench LXT®, DTL300Z

18V, 1/2", C ring/ PIN-detent 340
Nm , 0 - 3200 min⁻¹

Model DTL300 is an angle impact wrench powered by 18V
LXT Li-Ion battery



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1000 / 1500 / 3200 min ⁻¹
Max Fastening Torque Impact Drill	340 Nm
Nut-busting torque	530 Nm
Tightening Capacity Standard Bolt	M10 -M20
Capacity machine screw	M10 - M20
Tightening Capacity High Tensile Bolt	M10 -M16
Impacts per Minute (IPM)	0 - 1800 / 2800 / 4000 min ⁻¹
Drive Square	1/2 "
Sound Power Level (L _{WA})	108 dB(A)
Sound Pressure Level (L _{pA})	100 dB(A)

User benefits

- Ideal for working in tight spaces and overhead applications
- Variable speed control dial enables user to match the speed to the application for greater versatility
- Built-in LED light illuminates the work area
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions

EAN 0197050012548

Link to product - www.makita.com



Related products

■ Other

User manual

Parts drawing