

Chainsaw LXT®

DUC254RT

18V • 24 m/s • 25 cm / 10"

Handy brushless saw with a high chain speed for construction and forestry

An efficient brushless and cordless saw with a chain speed of 22.5 m/s. Its light weight and design with the handle on top make it easy to use. An instantaneous extra power is available for cutting thick branches. Equipped with a 10" guide bar.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max Output Power	570 W
Chain Oil Tank	140 ml
Max. Chain Speed (No Load)	24,0 m/s
chain bar length	250 mm (10")
Chain Pitch	3/8 / 0,325 "
Chain Gauge	0,043 "
Chain Gauge	1,1 mm
Number of Drive Links	40 / 46
Sound Power Level (L _{WA})	101 dB(A)
Sound Pressure Level (L _{pA})	93 dB(A)
Noise Uncertainty (K Factor)	2,5 dB(A)
Vibration Level, Cutting Wood	2,5 m/s ²
Vibration Uncertainty (K Factor),	1,5 m/s ²

EAN 0088381857567

Link to product - www.makita.com

User benefits

- Brushless maintenance-free and long-life motor
- Compact and lightweight for reduced operator fatigue
- Torque boost mode enables to cut thick branches by temporarily boosting current limiter
- Ideal for pruning application
- Top handle cordless chainsaw, only approved for commercial users with special training
- Adjustable automatic chain lubrication with large oil reservoir
- Battery protection system automatically shuts off power when the battery level is low



Related products

Standard AC

199075-5

Saw chain, -40, 3/8", 1,1 mm, 10" /



458501-6

Chain Protection Cover 10" / 25 cm



195093-1

Chain Oil Set, 1 L



161846-0

Guide bar 10" / 25 cm, 3/8", 1,1 mm



782023-7

Wrench 13 -16



831304-7

Accessory Bag



Standard MA

BL1850B

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

161846-0

Guide bar 10" / 25 cm, 3/8", 1,1 mm



195093-1

Chain Oil Set, 1 L



199075-5

Saw chain, -40, 3/8", 1,1 mm, 10" /



458501-6

Chain Protection Cover 10" / 25 cm



782023-7

Wrench 13 -16



Other

[User manual](#)

[Parts drawing](#)