

Hedge Trimmer Brushless LXT®

DUH506Z

18V, 500 mm, 4 000 min⁻¹



Technical specifications

Vibration Level, Hedge Trimming	≤ 2,5 / ≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Hedge Trimming	1,5 m/s ²
Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max Output Power	320 W
Strokes per Minute (SPM)	4000 min ⁻¹
Max blade opening	20 mm
Continuous Use 18V / 6.0 Ah Battery	75 min
Sound Power Level (L _{WA})	88 dB(A)
Sound Pressure Level (L _{pA})	80 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Product net weight	2,2 kg
Tool weight with battery	2,5 - 2,9 kg

User benefits

- Brushless maintenance-free and long-life motor
- Extreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Electric brake for maximum productivity and increased operator safety
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381772242

Link to product - www.makita.uk.com



Related products

■ Standard AC

413L91-8

Blade cover, 500 mm



■ Other

User manual

Parts drawing