Angle Grinder XGT®

GA041GZ01



Technical specifications

Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	3000 - 8500 min^{-1}
Max. Depth of Cut	31 mm
Disc Diameter	125 mm
Anti-Restart Function (NVR Switch)	✓
Electronic brake	✓
AWS ready	✓
Sound Power Level (L_{WA})	91 dB(A)
Sound Pressure Level (L_{pA})	83 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Disc Sanding	≤ 2,5 m/s^2
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s^2

User benefits

- Outperforming performance and efficiency similar to corded 1 000 W class grinder
- Excellent in continuous heavy-duty work
- Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth
- Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops
- Anti-restart function minimises accidental start-up
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Electric brake for maximum productivity and increased operator safety
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Soft start for smooth start-ups

EAN 0088381766715

Link to product - www.makitauk.com

Related products

Standard AC

158237-4
Grip 36 complete



835E79-0
Inner tray (4)



821552-6
Makpac case (4)



Other

User manual

Parts drawing