

# 80V Max (Twin 40VMax) Rotary Hammer BL XGT

## HR006GZ

HR006G is an SDS-MAX 52mm (2") cordless rotary hammer powered by two 40Vmax XGT Li-Ion batteries in series.



### TECHNICAL SPECIFICATIONS

Battery Type	Lithium-ion
Body only machine	✓
Voltage	80 (40Vx2) v
Max in concrete (TCT bit)	52 mm
Max in concrete (TCT core)	160 mm
Impact energy	20.0 J
Shank	SDS-MAX
Blows per minute	1,100 - 2,250 bpm
Noise sound pressure	99 dB(A)
Noise sound power	110 dB(A)
Noise K factor	3 dB(A)
No Load Speed	150 - 310 rpm
Vibration K factor	1.5 m/sec <sup>2</sup>
Vibration: Hammer Drilling	8.5 m/sec <sup>2</sup>
Vibration: Chiselling	7.0 m/sec <sup>2</sup>
Net weight	12.8 - 14.5 kg

### USER BENEFITS

- Auto-Start Wireless System (AWS) - connects to compatible dust extractors with Bluetooth. The dust extractor automatically runs while the switch is on.
- Brushless motor
- Variable speed
- Electric brake
- Soft start
- Constant speed control
- Torque limiter
- LED job light
- "Soft no load" function automatically reduces the motor speed during idling to suppress the vibration of the machine body.
- 2-mode operation: Rotation with hammering / Hammering only
- Active Feedback Sensing Technology (AFT): Shuts down the tool if the rotation speed suddenly slows down
- Anti-vibration housing and AVT for reduced operator fatigue

[Link to product - makitauk.com](https://www.makita.com)



# RELATED PRODUCTS

(Reco

## ■ OTHER