

Rotary Hammer Brushless XGT®

HR010GZ01

40Vmax, SDS-PLUS, 20 mm, 2.1J

Model HR010G is a 20mm SDS-PLUS combination hammer powered by 40Vmax XGT® Li-Ion battery.



Technical specifications

| | |
|---|----------------------------|
| Voltage XGT | ✓ |
| Nominal Battery Voltage | 40 V |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| No load speed | 0 - 1350 min ⁻¹ |
| Impacts per Minute (IPM) | 0 - 5000 min ⁻¹ |
| Max. Drilling Diameter in Wood | 26 mm |
| Max. Drilling Diameter in Concrete | 20 mm |
| Max. Drilling Diameter in Steel | 13 mm |
| Optimum Drilling Diameter Range in Concrete | 6 - 14 mm |
| Impact Energy | 2,1 J |
| Drilling diameter with TCT core bit | 35 mm |
| Adapted for SDS-PLUS bits | ✓ |
| Electronic brake | ✓ |
| AWS ready | ✓ |
| Sound Power Level (L _{WA}) | 101 dB(A) |

User benefits

- Built-in LED light illuminates the work area
- Battery protection circuit protects against overloading, over-discharging and over-heating
- Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth

EAN 0088381782135

Link to product - www.makita.com



Related products

■ Standard AC

413N42-3
DEPTH GAUGE



821552-6
Makpac case (4)



■ Other

User manual

Parts drawing