

Rotary Hammer SDS+ 26mm

HR2630

Model HR2630 is a 26mm (1") combination hammer based on predecessor model HR2610 but with improved operation mode change lever.



TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|-------------------------|
| Impact energy | 2.4 J |
| Max in concrete (TCT bit) | 26 mm |
| Max in concrete (TCT core) | 68 mm |
| Max in concrete (Diamond core) | 80 mm |
| Max in wood | 32 mm |
| Max in steel | 13 mm |
| Impacts per minute | 0 - 4,600 ipm |
| Input Wattage | 800 w |
| Net weight | 2.8 - 3.3 kg |
| No Load Speed | 0 - 1200 rpm |
| Vibration: Chiselling | 9.5 m/sec ² |
| Vibration: Hammer Drilling | 15.5 m/sec ² |
| Noise sound pressure | 91 dB(A) |
| Noise K factor | 3 dB(A) |
| Noise sound power | 102 dB(A) |
| Optimum Drilling Range | 4 - 18 mm |
| Vibration: Drilling into metal | 2.5 m/sec ² |

USER BENEFITS

- Modified operation-mode change lever enables switch from 'Rotation' to 'Hammering' mode and vice-versa without rotating the chuck.
- 3 mode operation: Rotation only / Rotation with hammering / Hammering only
- One touch sliding chuck for easy bit installation and removal.
- Variable speed control by trigger
- Forward / reverse rotation
- Torque limiter
- Double Insulation
- 40 different bit angle settings
- Compact and lightweight design
- Depth stop
- Ergonomically designed handle with rubberised soft grip fits your hand perfectly to provide maximum control and comfort.

[Link to product - makitauk.com](https://www.makita.com)



RELATED PRODUCTS

(Recom

■ OPTIONAL ACCESSORIES

195180-6
DUST COLLECTING CUP



■ OTHER