

Circular Saw XGT® , 40Vmax, 5 200 min⁻¹, 165 mm

HS012GZ



Technical specifications

Brushless Motor	✓
Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max Output Power	1300 W
No load speed	5200 min ⁻¹
Max. Cutting Depth at 90°	57 mm
Max. Cutting Depth at 45°	41 mm
Bore Size (Arbor Diameter)	20 mm
AWS ready	✓
Sound Power Level (L _{WA})	102 dB(A)
Sound Pressure Level (L _{pA})	91 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²

User benefits

- Twin LED lights with pre-glow and afterglow functions for better illumination and more accurate work
- Electric brake for maximum productivity and increased operator safety
- Brushless maintenance-free and long-life motor
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381776622

Link to product - www.makitauk.com



Related products

■ Standard AC

164095-8
Parallel Guide



196961-1
Dust Nozzle 35 / 40 Mm



783203-8
Hex Wrench 5 Mm



■ Other

[User manual](#)

[Parts drawing](#)