



Circular Saw

HS6601/2

1 050 W • 5 200 min⁻¹ • 165 mm

Light circular saw for professional use

An efficient and robust circular saw with a 1 050 W motor and speed of 5 200 min⁻¹ designed for professional use. Compatible with a blade with a 165 mm diameter that achieves a max. cutting depth of 54 mm. Compact design for added control and safety. Can be connected to guide rule with an adapter.

Technical specifications

Vibration Uncertainty (K Factor), Cutting Wood	1,5 m/s ²
Continuous Input Power	1050 W
No load speed	5200 min ⁻¹
Capacity 45°	37,5 mm
Max. Cutting Depth at 90°	54,5 mm
Max. Cutting Depth at 45°	37,5 mm
Max. Bevel Range (Left)	0 / 45 °
Blade Diameter	165 mm
Bore Size (Arbor Diameter)	20 / 30 mm
Sound Power Level (L _{WA})	107 dB(A)
Sound Pressure Level (L _{pA})	96 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Cutting Wood	≤ 2,5 m/s ²
Weight Without Cable	3,4 kg
Product Dimensions (L x W x H):	296 x 232 x 243

EAN 0088381806404

Link to product - www.makita.com

User benefits

- Angle adjustment from 0 ° to 45 °
- Cutting depth adjustment



Related products

■ Standard AC

164095-8
Parallel Guide



196520-1
Dust Nozzle



726082-1
Tipped Saw Blade 165

783217-7
Hex Wrench 5Mm



■ Other

[User manual](#)

[Parts drawing](#)