

40VMax Router XGT®, RP001GZ02

1/2"



Technical specifications

Vibration Level, Cutting Grooves in MDF	6,3 m/s ²
Vibration Uncertainty (K Factor), Cutting Grooves in MDF	1,5 m/s ²
Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max Output Power	1900 W
No load speed	8000 - 25000 min ⁻¹
Max. Collet Capacity	1/2 "
Plunge capacity	0 - 60 mm
Max. Collet Capacity	12 mm
AWS ready	✓
Sound Power Level (L _{WA})	100 dB(A)
Sound Pressure Level (L _{pA})	92 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

EAN 0197050005427

Link to product - www.makita.com

User benefits

- Soft start function minimises start-up shock and makes the tool start smoothly
- Anti-restart function minimises accidental start-up



Related products

■ Standard AC

122850-4
Dust Nozzle



122G61-3
Holder Assembly

1914M8-1
ACCESSORY SET

256861-8
Rod 8

342428-9
Straight Guide



4130A9-4
Chip Deflector

821552-6
Makpac case (4)



■ Other

User manual

Parts drawing