



## Router

# RP2303FC08/1

2 100 W • 12 mm

### Powerful Router for professionals

It has an Electric brake for maximum productivity and increased operator safety. Linear ball bearings for smooth plunge action and superior performance. Quick release plunge depth adjustment with micro control along with 3 preset depth stops for added precision.

### Technical specifications

Vibration Level, Cutting Grooves in MDF	4,2 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Cutting Grooves in MDF	1,5 m/s <sup>2</sup>
Continuous Input Power	2100 W
No load speed	9000 - 23000 min <sup>-1</sup>
Plunge capacity	0 - 70 mm
Max. Collet Capacity	12 mm
Sound Power Level (L <sub>WA</sub> )	99 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	88 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Product net weight	6,2 kg
Weight Without Cable	6,2 kg
Product Dimensions (L x W x H):	155 x 294 x 327 mm
Vacuum cleaner connection Ø in / out	32/37 mm
Power Supply Cord	4,0 m

**EAN 0088381782784**

Link to product - [www.makita.com](http://www.makita.com)

### User benefits

- Anti-restart function engineered to minimise motor start up when battery is inserted with switch locked on
- Combines power and precision for the most demanding routing applications
- Quick release plunge depth adjustment with micro control along with 3 preset depth stops for added precision
- Electric brake for increased productivity and operator safety



# Related products

## Standard AC

**122850-4**  
Dust Nozzle



**342428-9**  
Straight Guide



**344364-5**  
Templet Guide 14,5 x 16 x 13 mm



**763803-0**  
Collet sleeve for 1/4" bit



**763805-6**  
Collet Sleeve 3/8"



**821552-6**  
Makpac case (4)



**8352F0-3**  
Makpac Type 4 Inner Tray (4)



---

## Other

**User manual**

**Parts drawing**