

# Wall Chaser 125mm

## SG1251J

Model SG1251 has been developed based on SG1250. In addition to the benefits of the current model, SG1251 features an improved trigger switch operable with the fingers of the hand holding the top handle.



### TECHNICAL SPECIFICATIONS

Blade Diameter	125 mm
Max. Cutting Depth	30 mm
Bore Diameter	22.23 mm
Noise sound pressure	97 dB(A)
Noise sound power	108 dB(A)
Noise K factor	3 dB(A)
Cutting diameter	Every 3mm from 6 to 30 mm
Input Wattage	1,400 w
No Load Speed	10,000 rpm
Vibration K factor	1.5 m/sec <sup>2</sup>
Vibration: Cutting Concrete	5.0 m/sec <sup>2</sup>
Net weight	4.5 kg

### USER BENEFITS

- Improved trigger switch with dust cover to prevent ingress of dirt and dust.
- Aluminium blade case designed to allow for easy blade replacement and cutting depth adjustment.
- Adjustable width and cutting depth.
- SJS system to prevent motor burn out
- Ergonomically designed handle
- Rubberised soft grip
- Connectable to dust extractor
- Double Insulation
- Soft start feature.
- Constant speed control
- Electronic current limiter for overload protection.

[Link to product - makitauk.com](https://www.makita.com)



# RELATED PRODUCTS

(Reco

## ■ STANDARD ACCESSORIES

821552-6

MAKPAC CONNECTOR CASE (TYPE



838111-9

INNER TRAY



## ■ OTHER