

# Impact Driver XGT®, TD004GZ01

40Vmax, 230 Nm

Model TD004G is a brushless Impact driver powered by a 40VMax XGT Li-Ion battery



## Technical specifications

Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1200 / 2100 / 3000 / 3900 min <sup>-1</sup>
Max Fastening Torque Impact Drill	60 / 130 / 210 / 230 Nm
Tightening Capacity Standard Bolt	M5 - M20
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 1900 / 3100 / 3600 / 3900 min <sup>-1</sup>
Driving Shank	1/4 "
Sound Power Level (L <sub>WA</sub> )	108 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	100 dB(A)

**EAN 0197050008237**

Link to product - [www.makita.com](http://www.makita.com)

## User benefits

- Electronic 4 stage impact power selection for added versatility
- Ergonomic soft grip handle provides increased comfort
- Built-in LED light illuminates the work area
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions



# Related products

## ■ Standard AC

266622-8

Truss Head Screw M4 X 12



346317-0

Belt Hook



821550-0

Makpac case (2)



835R29-3

Inner tray (2)



---

## ■ Other

[User manual](#)

[Parts drawing](#)