

# Dust Extractor 42L M-Class

## VC4210MX/2

Wet and Dry M-Class Dust Extractor with power take-off

Class M - Removes 99.9% of dust with Limit Value for occupational exposure > 0.1 mg/m<sup>3</sup>.

Suitable for processes involving mica, china clay, gypsum, wood dust, such as softwood and hardwood and silica dust, such as masonry, concrete.  
Dust Extractor 42L M-Class



### TECHNICAL SPECIFICATIONS

Power take-off wattage	1800 w
Max Airflow	4.5 m <sup>3</sup> /min
Dust Bag Capacity	30 litres
Max Sealed Suction	25 kPa
Tank Capacity	42 litres
Tank capacity Wet	29 litres
Input Wattage	1200 w
Net weight	16 kg

### USER BENEFITS

- Approved for Dust Classes M in accordance with the EU standard.
- Automatic filter cleaning system.
- Durable PTFE filter with high filtration efficiency. Washable non-stick membrane
- Flat top design for deposit of hand tools and accessories.
- Hatchback with big opening for easy access to filter
- Individual settings for different hose diameters (21,27,32, 36 and 38mm)
- Speed regulation
- Air flow sensor beeps when air flow is reduced by clogged filter, full tank etc.
- Automatic On/Off function: machine activates when a connected power tool is used.
- Integrated hose, cable and accessory storage
- Double-wall container with big wheels and steel castors.
- Makpac cases can be attached to the unit with optional adapter plate

[Link to product - makitauk.com](https://www.makita.com)



# RELATED PRODUCTS

(Recon

## ■ OTHER