

Quick reference chart

Sterling Profile 1
screened

3 compartment

Profile 1 CS13
167 x 50mm

Base unit

Pack 1 x 3m



ETB1MCS13

Main compartment cover

Pack
Unscreened 8 x 3m

ETL1WH

Angled cover

Pack 1 x 3m

2 x
ETAC1CSWH

Screening

Conductive spray (CS) is unique to Marshall-Tufflex and is applied in the factory to provide screening from electromagnetic interference to data and communications cabling within trunking systems. The coating is applied to a range of data boxes, covers, clip-on components and fabricated fittings.



WARNING: A CS coating is not suitable for low voltage circuits.
BS7671:2008. For data/voice use only.

Screened compartments key to coding

CS13 = screening in compartments 1 and 3

1 gang screened accessory box

...DATA...

code	depth	pack
ESSB1SWH*	30mm	20

2 gang screened adjustable accessory box

...DATA...

code	depth	pack
ESSB2SWH*	30mm	10

*Supplied complete with earth terminal



Steel screening divider

code	pack
ESF1	5

Note: optional steel screening divider to assist in compliance with BS EN 50174-2



Steel screening divider bonding strap

code	pack
ESF2	5



Bonding strap

code	pack
ESBS1	5

p278

Technical
Information